

4500 WRC

Wireless Remote Control

4500 Wireless Remote Control allows you to perform, with safety and precision, low-speed maneuvers such as docking, anchoring or mooring from the most convenient position of your boat



Available configurations



WRC 5F

- PORT ENGINE
- STARBOARD ENGINE
- BOW THRUSTER
- ANCHOR WINCH



WRC 6F

- PORT ENGINE
- STARBOARD ENGINE
- BOW THRUSTER
- STERN THRUSTER
- ANCHOR WINCH

TECHNICAL DATA

- Dimensions (L.W.A.)..... 157 x 80 x 44 mm
- Casing material..... Charged Nylon UL 94 HB
- Degree of protection IP 65
- Weight (battery included)..... ≈340 g max
- Operating and storage temperature -25°C - +70°C / -40°C - +85°C
- Operating frequency I.S.M. 2.4 GHz, 16 ch
- Number of programmable channels 16
- Transmission Mode Half Duplex
- Autonomy at 20°C ≈18 hours

SUPPLY KIT

- 1 TRANSMITTING UNIT
- 1 RECEIVER UNIT
- 2 RECHARGEABLE LI-ON BATTERY
- 1 BATTERY CHARGER
- 1 USER MANUAL

FLEXBALL

Flexball Italiana

info@flexballitaliana.com - www.flexballitaliana.com